

## RF Micro-strip Power Splitter Series

### Microwave Passive Components



<b>Item Name</b>	2 Way of RF Micro-strip Power Splitter
<b>Item Number</b>	KPD0225N
<b>Technical Parameters</b>	Frequency Range: 800-960 & 1710-2500 MHz Apportionment Loss: 3dB Added Loss: Max 0.25dB (824-960MHz) Max 0.3dB (1710-2200MHz) Max 0.4dB (2200-2500MHz) VSWR (max.): 1.25 Isolation (min.): 20dB Power Capacity: 25 W Surface Mount: 50Ω Connector Type: N-50KF Dimensions: 58.2 x 58.2 x 20.4



<b>Item Name</b>	3 Way of RF Micro-strip Power Splitter
<b>Item Number</b>	KPDO330N
<b>Technical Parameters</b>	Frequency Range: 800-960 & 1710-2500 MHz Apportionment Loss: 4.77dB Added Loss: Max 0.25dB (824-960MHz) Max 0.45dB (1710-2200MHz) Max 0.6dB (2200-2500MHz) VSWR (max.): 1.25 Isolation (min.): 20dB Power Capacity: 25 W Surface Mount: 50Ω Connector Type: N-50KF Dimensions: 95.2 x 45.2 x 20.4



<b>Item Name</b>	4 Way of Micro-strip Power Splitter
<b>Item Number</b>	KPD0425N
<b>Technical Parameters</b>	Frequency Range: 800-960 & 1710-2500 MHz Apportionment Loss: 6dB Added Loss: Max 0.3dB (824-960MHz) Max 0.5dB (1710-2200MHz) Max 0.6dB (2200-2500MHz) VSWR (max.): 1.25 Isolation (min.): 20dB Power Capacity: 25 W Surface Mount: 50Ω Connector Type: N-50KF Dimensions: 94 x 77 x 22



<b>Item Name</b>	4 Way of Micro-strip Power Splitter
<b>Item Number</b>	KPD0430N
<b>Technical Parameters</b>	Frequency Range: 800-960 & 1710-2500 MHz Apportionment Loss: 6dB Added Loss: Max 0.3dB (824-960MHz) Max 0.5dB (1710-2200MHz) Max 0.6dB (2200-2500MHz) VSWR (max.): 1.25 Isolation (min.): 20dB Power Capacity: 25 W Surface Mount: 50Ω Connector Type: N-50KF Dimensions: 94 x 77 x 22